

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.

1300 I STREET, N. W.
WASHINGTON, DC 20005-3315

202 • 408 • 4000
FACSIMILE 202 • 408 • 4400

WRITER'S DIRECT DIAL NUMBER:

(202) 408-4130

April 6, 2000

JC542 U.S. PTO
09/544292
04/06/00

TOKYO

011•813•3431•6943

BRUSSELS

011•322•646•0353

ATLANTA
404•653•6400
PALO ALTO
650•849•6600

ATTORNEY DOCKET NO. 02100.0048

Box PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Re: New U.S. Patent Application
Title: SORT SYSTEM AND METHOD UTILIZING
INSTRUCTIONS TO DIRECT PLACEMENT
AND PROVIDE FEEDBACK
Inventors: Brett B. BONNER, Ole-Petter SKAAKSrud,
Daniel L. SPECHT, David J. DUTTON,
and Mark J. THOMAS

Sir:

We enclose the following papers for filing in the United States Patent and Trademark Office in connection with the above patent application.

1. Application - 34 pages, including 2 independent claims and 31 claims total.
2. Drawings - 15 sheets of informal drawings (Figures 1-15).
3. A check for \$958.00 representing a \$760.00 filing fee and \$198.00 for additional claims.

Applicant claims the right to priority based on Provisional Patent Application Serial No. 60/128,213 filed April 7, 1999.

This application is being filed under the provisions of 37 C.F.R. § 1.53(f). Applicants await notification from the Patent and Trademark Office of the time set for filing the Declaration.

Please accord this application a serial number and filing date.

Page 2

RFR/MKC/dbc
Enclosures

UNITED STATES PATENT APPLICATION

OF

BRETT B. BONNER,
OLE-PETTER SKAAKSUD,
DANIEL L. SPECHT,
DAVID J. DUTTON, and
MARK J. THOMAS

FOR

SORT SYSTEM AND METHOD UTILIZING INSTRUCTIONS
TO DIRECT PLACEMENT AND PROVIDE FEEDBACK

CROSS REFERENCE TO RELATED APPLICATION

This patent application claims priority to Provisional U.S. Patent Application Serial No. 60/128,213, entitled "Sort System Utilizing Instructions to Direct Placement and Provide Feedback", filed on April 7, 1999, which is herein incorporated by reference.

BACKGROUND OF THE INVENTION

When a person wants to send an object to someone else (the "addressee"), they wrap up the object and address it. Then this person, which we will call the customer, either drops off the object to a place where it is stored temporarily or the delivery company (the "deliverer") picks it up and drops it off there. In the case of the U.S. Postal Service, this storage location would usually be the local Post Office.

At the storage location this object and many others are gathered, and must then be sorted. They must be sorted to decide where to send each object, so each object must be looked at to decide which plane, truck, or train to put it on so that it goes to the area where the addressee lives. For example, if a customer in Spokane, Washington wants to send a 4 by 6 inch picture frame to a friend in Kennebunk, Maine the customer wraps it, addresses it, and either drops it off at the deliverer's Spokane office, or has the deliverer pick it up. By the end of the day the deliverer has, let us say, 6200 objects in its central Spokane office. Let us also say that of the 6200 objects, 112 are destined for the Portland, Maine, area of which three are destined for Kennebunk. The deliverer must sort the objects to separate from the 6200 the 112 to be sent to Portland, Maine. When the 112 objects arrive from Spokane in Portland, the Portland office will

have received, let us say, 1430 additional objects from the rest of the world that are destined for delivery addresses in the Portland area.

5 The objects in the Portland office must be sorted again, to decide which delivery vehicle to put each object on. One of these vehicles is scheduled to drive to Kennebunk. Thus, after sorting the 1430 objects from the rest of the world, plus the 112 from Spokane, 38 are destined for Kennebunk, only three of which (including our customer's picture frame) is from Spokane. These 38 are placed in the Kennebunk-bound delivery vehicle which then delivers the picture frame and the 37 other objects to addresses in Kennebunk.

In this example, the picture frame only went through two sortings: one in Spokane and one in Portland; but a typical object may go through many more. Delivery companies, not surprisingly, have developed methods and machines to sort objects.

15 Delivery companies, especially those delivering large quantities of small objects, usually use one of two methods to sort objects. In the first, a person picks up each object, reads information off of the object, decides where to place the object, and then places the object in an appropriate sort destination (like, for instance, a bin bound for Portland or Kennebunk). The second conventional method uses a fully automated system where a machine, rather than a person, performs the above tasks. The drawbacks of the first method include human error, slow reading, and slow decision making. The second method, *i.e.*, the fully automated system, is not without failings as well, most notably that it is expensive.

SUMMARY OF THE INVENTION

5 The advantages and purposes of the invention will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The advantages and purposes of the invention will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims.

To attain the advantages and in accordance with the purposes of the invention, as embodied and broadly described herein, the invention comprises a method for sorting objects, which includes capturing object information from a machine readable indicia on an object, determining routing information from the information, determining, based on the routing information, a correct sort destination for the object, and generating a visual and/or audio command identifying the correct sort destination for the object.

The invention also comprises an object sorting system comprising a rack system, comprising a plurality of sort destination modules, each sort destination module further comprising a sort destination capable of holding one or more objects, a management system comprising a control system, an information capture device for reading machine-readable indicia from each object and for outputting the information to the control system, and an audio system for providing instructions to an operator.

20 It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate one embodiment of the invention and together with the description, serve to explain the principles of the invention. In the drawings,

Figure 1 is a flow-chart of an automation system in accordance with the present invention;

Figure 2 is a flow-chart of the control system initialization process shown in Figure 1;

Figure 3 is a flow-chart of the sort selection / sort destination initialization process shown in Figure 1;

Figure 4 is a flow-chart of a method of sorting objects in accordance with the present invention;

Figure 5 is a flow-chart of a sorting system in accordance with the present invention;

Figure 6 is a flow-chart of the capture indicia from object / lookup routing process shown in Figure 1;

Figure 7 is a flow-chart of the object placement / weighing process shown in Figure 1;

Figure 8 is a flow-chart of a misplaced object correction process in shown in Figure 1;

Figure 9 is a flow-chart of the tare process shown in Figure 1;

Figure 10 is a flow-chart of the sort destination close-out process shown in Figure 1;

Figure 11 is a flow-chart of the object database and upload process shown in Figure 1;

Figure 12 is a flow-chart of the end sort process shown in Figure 1;

5

20

Figure 13 is a side view of a rack sorting system in accordance with the present invention;

Figure 14 is a block diagram of system architecture of a rack-sorting system in accordance with the present invention; and

Figure 15 is a diagram of input/output points and related architecture of a controller area network interface board shown in Figure 14.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference will now be made in detail to the present preferred embodiment of the invention, an example of which is illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

In a manual system for handling the processing of objects, a person reads information off of an object and then decides where to place the object. The difficulty with this system is that people tend to make mistakes and are slow, at least compared to a fully automated system, in reading object labels and in deciding where to place the objects. In an automated system, a machine reads information from an object, decides where to place the object, and places the object. The present invention comprises a "soft" automation sorting system. As used herein, the term "soft" is used to describe a hybrid system using people to physically sort objects and a control system to manage the sort.

In accordance with the present invention, a method for sorting objects comprises the steps of capturing object information from machine-readable indicia on an object, determining routing information from the information, determining, based on the routing information, a correct sort destination for the object, generating a visual and/or audio command identifying the correct sort destination for the object, and verifying that the object is placed into the correct sort destination.

In more detail, the soft automation system reads information off of an object using an information capture device (e.g., a scanner). It then processes the information and decides where the object should be placed. The system then alerts the person responsible for placing the objects (the "operator") with visual and/or audio instructions, telling the operator into which sort destination (also referred to as a "bin") to place the object. If the system includes sensors to detect where objects have been placed, the soft automation system will recognize when the operator places an object into a wrong sort destination. When an object is placed in the wrong sort destination the system will inform the operator, signaling him or her to correct it. Thus, the soft automation system significantly speeds up the sorting process by reading the object label and deciding where each object goes and reduces errors.

If the object was placed in the correct sort destination, the soft automation system recognizes this and informs the operator that the object has been placed in the correct sort destination. This process of capturing information from the indicia of an object, processing the

information from that object, instructing the operator where to place the object, and insuring that the object is in the correct sort destination, is usually repeated until all of the objects have been sorted.

To manage this sorting process, control system 2 manages where objects are to be placed but also does much more. For instance, once an object has been correctly placed in a sort destination, control system 2 receives the weight from the sort destination's scale, so that control system 2 will know the object's weight. By so doing, the control system 2 can keep track of the weight of every object, which can help in deciding into which plane or delivery vehicle the object should be placed and, further, helps the delivery company know when to charge the customer for an overweight object.

The preferred embodiment for sorting objects will be discussed as an aspect of an embodiment for the soft automation system. An embodiment of the soft automation system includes a method for sorting objects, and will now be discussed in general terms; the details of each step, which make up how the system operates, will be discussed later. The soft automation system is illustrated in figure 1, and the preferred embodiment for a method of sorting objects is represented by capture indicia on object / lookup routing sort automation system step 102 as well as the object placement aspect of object placement / weighing process step 104.

The embodiment of the machine part of the soft automation system may be used to implement the above method. This machine part is activated by initializing control system 2, which manages the entire soft automation system. After initialization step 106 is complete, the

operator logs in, step 108. The operator and control system 2 then work together to initialize the sort destinations, step 110, figure 1.

Once these preliminary initializing steps are completed, control system 2 idles in idle state step 112, waiting to begin sorting objects. Usually, the operator scans an object's indicia which prompts the control system 2 to begin step 102.

In capturing information from an object's indicia, step 102, illustrated in figure 1, control system 2, with the aid of the operator or a conveyor belt, captures object information from machine-readable indicia on an object to be sorted, determines routing information from the object information (e.g., a postal code, tracking number, or sort destination), and uses that routing information to determine in which sort destination the object should be placed. The routing information usually includes the path that the object will travel after reaching the sort destination. In cases where the object will not travel after being placed into its sort destination, the routing information will not include this path because there is none (this will often be the case when this method is used to sort objects at the final destination for the objects, such as in a storage facility). Capturing information from indicia on objects, step 102, is typically repeated until all of the objects have been sorted into their correct sort destinations.

After an object (also called a document or package) has been scanned to capture its information from its indicia and placed in a sort destination, control system 2 determines whether the object is in the correct sort destination. If the object is in the correct sort destination its weight is measured and sent to control system 2. If it is not in the correct sort destination,

control system 2 instructs the operator to correct the error according to misplaced object correction process step 122. The process of weighing object and checking that it is in the correct sort destination is represented by object placement / weighing process step 104 of figure 1. When the object is in the correct sort destination and its weight has been recorded, control system 2 returns to idle state, step 112.

After all of the objects have been placed correctly, the operator and control system 2 close out each sort destination (sort destination close-out process step 148). After completing this step control system 2 idles, idle state step 112, or ends the process, end sort process step 150. The end sort process step 150 is completed by control system 2, thereby ending the current sort session (sort completed step 126). Control system 2 then updates/uploads the object database (step 124), by communicating with scan central server 154.

Each step performed by the soft automation system will now be discussed in more detail. Referring to Figure 2, initialization system process step 106 begins when the operator turns on control system 2, step 106-01. First, control system 2 runs a diagnostic program, step 106-02, to check other components used in the soft automation system. Control system 2 checks to be sure that a printer port, user interface, and audio system are working properly. Control system 2 also checks required files within its memory. If the components and required files are judged error-free, step 106-03, control system 2 waits for the operator to log in, step 106-04. If the diagnostic fails, control system 2 resets and ends the process, steps 106-05 and 106-06.

Referring to Figure 3, after the soft automation system is initialized according to step 106 and the operator logs in, step 108, the operator and control system 2 work together to complete a sort selection and sort destination (also referred to as "SD" in most of the figures) initialization process step 110. In step 110 the operator selects which type of sort he or she wants to do, sort definition step 110-01, and then control system 2 checks each sort destination for its deviation in weight from the weight of an empty sort destination (the sort destination's calibrate zero), step 110-02. In order to complete the sort destination initiation process, control system 2 makes two assumptions: i) the calibrate zero does not drift more than a set amount, for example, 0.75 or more pounds and ii) empty crates have a given weight range, for example, between 1.5 and 2.5 pounds. Control system 2 checks the weight of each sort destination, one at a time. If the weight is not off, *i.e.*, the deviation is 0.75 or less pounds from the calibrate zero, control system 2 assumes that the sort destination does not contain a crate (see step 110-03). If so, control system 2 requests that the operator place a crate in each sort destination, step 110-04. Control system 2 will make this request with a combination of audio, visual, and/or user interface-based commands. The operator may place a crate in the sort destination or over-ride the request by canceling the command, step 110-05, in which case control system 2 will mark the sort destination's status as unknown, step 110-06. Control system 2 waits for the scale to stabilize (step 110-07) and then checks again to determine if the deviation is within the range of an empty crate, step 110-08. If neither condition is met, control system 2 marks the sort destination status

as unknown, step 110-06. If either condition is satisfied, control system 2 tares the scale (set the scale to zero) and marks the sort destination as available to place objects into (step 110-09).

If, on the other hand, the deviation is greater than 0.75 pounds, control system 2 marks the sort destination status as unknown, step 110-11, so long as the deviation is not within the range of the weight of an empty crate (step 110-10). If the deviation is within the range of the weight of an empty crate, (step 110-10), it will tare the scale and flag the sort destination as ready (step 110-12), provided that the sort destination has an empty crate in it. Control system 2 continues this procedure until the status of all of the sort destinations have been marked as either ready or unknown (step 110-13).

Once the status of the sort destinations has been marked, control system 2 activates a visual indicator, such as an indicator light, (step 110-14) that correspond to the unknown-status sort destinations to alert the operator or a quarterback (the person who aids the operator by handling the crates, usually from opposite side of the sort destination from the side that the operator operates on) that the sort destination status is unknown. The operator or quarterback then corrects the problem and then enters "done" via the user interface, step 110-15. Control system 2 then resets the scales on the unknown-status sort destinations (step 110-16). If the reset was not successful (checked at step 110-17) control system 2 marks that sort destination to permit it to operate in non-weigh mode (step 110-18). If the reset is successful control system 2 enables the scale and checks the deviation (both according to step 110-19) and, if the deviation is now within the range of an empty crate, step 110-20, tares the scale and marks the sort

destination ready, step 110-21. If the deviation is still not within the range of an empty crate, control system 2 marks the sort destination to operate in non-weigh mode, step 110-18. After completing these steps, control system 2 returns to idle state step 112. When in idle state step 112 control system 2 waits for input from the operator, quarterback, or for an object to be scanned. The operator may then begin the step that encompasses a method for sorting objects.

In the preferred embodiment further illustrated in figures 4, 5, and 6, a machine-readable indicia capture device (not shown) is used to capture (*e.g.*, scan) object information from machine-readable indicia (*e.g.*, a bar-code) from an object, step 128-01 and step 102-01. The information capture device is preferably mounted overhead for capturing the information from indicia on each object as it moves along a conveyor belt under the information capture device. Alternatively, the indicia could be read by a hand-held information capture device or other reader capable of capturing information automatically. For example, an operator may hand-scan each object with a hand-held information capture device, especially if the number of objects needing to be scanned is small. Although a moving conveyor belt is used in the preferred embodiment, an operator or other appropriate machine may move the object across the reader. In short, any method allowing a computer to access information would suffice to complete step 128. The preferred machine-readable indicia is a bar-code using an ASTRA data string of 32 digits. Any machine-readable indicia that provides sufficient information for control system 2 to ascertain the needed information for determining sort destination alternatively may be employed.

After an object is scanned, the information capture device sends data representing the indicia (step 102-03) to control system 2. Control system 2 interprets the indicia, step 102-02, to find the object information. Control system 2 then determines the routing information either by comparing the object information against a routing database (remote or local, but preferably local), or preferably without comparing the object information to the routing database in cases where the routing information is included in the object information (see figure 6). The routing information may be adjusted by control system 2 based on the sort type and geographical location where the sort is performed. The routing information includes the eventual destination which corresponds to a sort destination, but not necessarily where the sort destination is located in the sort destination module (*i.e.*, which column and row in the module, usually represented by a number). To remedy this, control system 2 uses the routing information to determine the correct sort module which control system 2 then accesses to find the correct sort destination number corresponding to the eventual destination for the object (step 102-10). Once control system 2 knows the correct sort destination number for the object, it sends a tare to the scale of the correct sort destination, step 102-11 (*i.e.*, the sort destination's weight is reset). A command identifying the correct sort destination for the object is generated by control system 2, and control system 2 waits for the object to be placed in any of the sort destinations (object placement / weighing process step 104). Control system 2 preferably informs the operator as to where to place the object by an audio instruction, such as "place object in sort destination number eight" (step 102-12) and by activating a light located adjacent the appropriate sort destination,

(step 102-13). Any other appropriate means of informing the operator as to where to place the object could also be used.

Referring to figure 7, after an object has been scanned and control system 2 has determined where the object should be placed and has informed the operator, control system 2 waits for the operator to place the object in a sort destination (step 104-01). It then verifies correct sorting, namely, that the object is in the correct sort destination (step 104-02). Preferably, control system 2 verifies according to the processes illustrated in figure 1 and more specifically in figures 7 and 8—the misplaced object correction process step 122 and the object placement / weighing process step 104. In step 104, control system 2 uses photo sensors (not shown) to determine which sort destination the operator placed the object in. Alternatively, however, any sensor capable of sensing whether an object is placed within a sort destination, such as a scale or motion detector, would also suffice. Assuming the object was placed in the correct sort destination, control system 2 checks the tare flag (step 104-03). The tare flag is set to indicate if the scale tare (step 102-10) was successful. If the tare flag indicates that the scale tare was not successful, control system 2 sets the weight of that object to zero (step 104-04), updates the object database (step 104-05), and idles (step 112), typically to wait for another object to be sorted. If the tare flag indicates that the scale tare was successful, control system 2 waits for the scale to stabilize, step 104-06, receives the weight from the scale for that object, and sets the object's weight in the object database to that weight, step 104-07, and returns to idle state step 112, again usually to wait for another object to be sorted.

If the object is placed in an incorrect sort destination, control system 2 follows the misplaced object correction process step 122, illustrated in figure 8. If an object is not placed in the correct sort destination, control system 2 invokes the misplaced object correction process step 122. Here control system 2 attempts to help the operator find the particular object that was incorrectly placed in a sort destination. Photo sensors on each sort destination are linked to control system 2. When control system 2 detects, through one of these sensors, that the object has been placed in a wrong sort destination (step 122-01), a light located along the sort destination that the object was incorrectly placed into flashes, step 122-02. At this point the operator notes the mistake and retrieves the object from the incorrect sort destination (step 122-03). To make sure that the correct object was retrieved, the operator scans the retrieved object (step 122-04). Control system 2 then compares the machine-readable indicia with that of the correct object (step 122-05). If they are the same, the light at the incorrect sort destination is turned off (step 122-06) and control system 2 returns to step 102 whereby control system 2 again determines where to place the retrieved object and so instructs the operator. If the retrieved object does not have the same indicia as the incorrectly-placed object, control system 2 removes the object information associated with the retrieved object from the database (step 122-07) and the operator is instructed to place the object back with the non-sorted objects, step 122-08. The operator continues to retrieve objects from the incorrect sort destination that were placed into that sort destination until the improperly-placed object is retrieved, or until three objects have been incorrectly removed from the incorrect sort destination (control system 2 checks according to

step 122-09). In either case, control system 2 cancels the object retrieval step 122-10, turns off the flashing light on the incorrect sort destination, and returns, step 122-11, to step 102.

The tare scale process step 120 has been described briefly above. Referring to Figure 9, in the tare scale process step 120, control system 2 waits for the scale to tell control system 2 the status of the scale, tare response step 120-01. If the tare was not successful, *i.e.*, the scale does not read a stable weight within an acceptable range, control system 2 checks the scale according to step 120-12, and sets the tare flag to failed, step 120-03. If it was successful, *i.e.*, the scales working properly and the scale tare was successful, control system 2 sets the tare flag to successful (step 120-08). In both instances, the tare scale process then continues to wait for additional input, such as from a new object being placed in the sort destination which changes the weight which the scale reads. Each new input called a tare response, step 120-01.

The soft automation system goes through many repetitions of the above processes. As the method for sorting objects is repeated, many objects are sorted and the crates fill up. Preferably, the soft automation system uses the illustrated process of figure 10 to close out a sort destination when its crate fills up. In this process control system 2 must first determine when the sort destination is full. There are three ways to do this in the preferred embodiment. First, control system 2 receives information from the scale indicating that the sort destination's weight has reached a certain amount. Once this happens, control system 2 closes out the sort destination used and informs the operator by illuminating a light, sort destination close out step 148. In the second way, the operator presses a pushbutton light associated with the sort destination when the

10

15

20

objects in that sort destination. Once the scale indicates that an empty crate is in the sort destination, control system 2 turns off the sort destination light (pushbutton indicator 28), step 148-15, and sets the sort destination to a "ready" status, so that the operator may sort objects into the sort destination (see step 148-16). When all of the objects in a lot have been sorted, control system 2 is informed by the operator. Control system 2 then shuts down the sorting operation, proceeds with end sort mode 148-17, and returns to end sort process step 150 to finish the sort. If not, control system 2 returns to idle state step 112, to step 148-18, and waits to sort more objects.

Referring to Figure 11, during sort destination close-out process step 148, and document placement / weighing process step 104, control system 2 records information about each object into a database, steps 104-05 and 148-10. In this process control system 2 uses the database to generate data in an appropriate record format, step 152-01, and sends this formatted record through a wide area network, step 152-02, to a scan central server 154. This server communicates with a tracking database 156 and a billing database 158. Pertinent information sent to the databases includes the weight of the objects. The weight data can be used for revenue recovery, as scales 24 used in the soft automation system are legal for trade. Likewise, other pertinent information, such as when an object was processed and where, can be used to track the object, and is recorded in tracking database 156.

Referring to Figure 12, as noted previously, the soft automation system closes each session of sorting according to end sort process step 150. In this process the operator initiates the sort process through the user interface, step 150-01, *e.g.*, by pressing a button. Control system 2 then marks all of the sort destinations as being in a close-out state, step 150-02, and follows the sort destination close-out process step 148. Once the sort destination close-out process step 148 is complete, control system 2 checks each sort destination's status. If all sort destinations are closed, step 150-04, a statistical summary of the sort session is generated and printed, step 150-05, and the sort is complete, step 150-06. If each sort destination's status is not closed, it returns to the sort destination close-out process step 148 until each is closed-out. Control system 2 proceeds to statistical summary step 150-05 in which data is generated concerning how the entire sort was completed, and includes such information as how long the sort took to complete, how many errors were made, which objects were over-weight, how many objects were sorted, where they were sorted to, and other similar information.

The embodiment of the above method uses a machine as well as people, the specific machine and its peripheral structure used to complete this method are described below.

In accordance with the present invention, an object sorting system comprises a rack system, comprising a plurality of sort destination modules, each sort destination module further comprising a sort destination for holding at least one object, and a management system comprising a control system, an information capture device for reading machine-readable indicia

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
215

from each object and for outputting the information to the control system, and an audio system for providing instructions to an operator.

In the preferred embodiment illustrated in figure 13, rack system 10 includes a primary rack 12 including a number of sort destination modules 20. Each sort destination module 20 contains a sort destination 22, a scale 24, a placement sensor 26, an indicator 28, and additional indicators (push-button indicator 30 and alert indicator 32). Sort destination 22, which is a rectangular or cubical enclosure provided within each sort destination module 20, is adapted to accommodate a crate 34. This illuminated indicator 28 is a pushbutton light which informs the operator that an object should be placed in the sort destination. It is located at or near the front-side of sort destination 22 so that the operator, who works at the front sides of the sort destinations, can easily see and reach it. Indicator 28 also acts as an input, *i.e.*, it is a push-button illuminated switch. Where an operator presses indicator 28, control system 2 is alerted that a task will be completed by the operator. Placement sensor 26 is a proximity-type sensor, preferably a photo-eye sensor, which monitors when an object is placed in the sort destination. As a backup, scale 24 also monitors when an object is placed in the sort destination, as a result of the sort destination becoming heavier. Both placement sensor 26 and scale 24 communicate this information to control system 2, as discussed more fully below. Scale 24 also senses when and if a crate 34 has been placed in its sort destination 22, and how much the crate weighs. This permits keeping track of the weight of objects so that the delivery company can charge an appropriate fee. Another lighted push-button switch, push-button indicator 30, is mounted

adjacent the back side of the sort destination module so that the quarterback, who works on the back-sides of the modules, can receive from and input information to control system 2. Another light, alert indicator 32, is also mounted adjacent the back of the sort destination for use by the quarterback.

5

The object sorting system also includes wiring for connecting rack system 10 with control system 2, as well as mounting locations for an overhead information capture device 36, user interface 38, and sound system 40. Overhead information capture device 36 (not shown in figure 13, see figure 14) scans an object's indicia, user interface 38 is used by the operator to communicate with control system 2, and sound system 40 is used by control system 2 to communicate with the operator through audible messages.

By communicating with scale 24, control system 2 determines which sort destination an object was placed in, the time when the object was placed, and its weight. Scale 24 outputs the weight of: each object placed within sort destination 22, crate 34, and the total weight of the objects within crate 34. This information is communicated to control system 2.

Control system 2 also communicates with information capture device 36, as shown in the preferred embodiment of figures 14, which reads the bar-code or other machine-readable indicia on each object. Alternatively, any type of information capture device capable of reading machine-readable indicia and capable of transmitting needed information to control system 2, to allow a determination on which sort destination 22 is the correct sort destination to place to object into, may be used.

20

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, D. C. 20005
202-408-4000

User interface 38 of the management system preferably allows the operator (also called the user) to input his or her identity into control system 2. User interface 38 also acts as a communication device between the operator and control system 2 via a terminal display, a keyboard, and an audio system (in conjunction with the other communication devices such as the pushbutton lights).

The preferred rack system includes machine-readable indicia printer 54, a printer lighted button (not shown), an uninterruptible power supply (UPS) 56, an Ethernet connection 46, and a serial diagnostics port 48. Control system 2 outputs commands to the printer 54 and the UPS 56, and communicates externally through the Ethernet connection 46.

Referring to Figures 14 and 15, control system 2 preferably communicates and controls rack system 10 via a controller area network bus (not shown), a controller area network addressing board 42, and a controller area network adaptor card (not shown) and an interface board 44 for each sort destination 22. Addressing board 42 distributes power and communications between each rack and control system 2. Control system 2 uses addressing board 42, in conjunction with the controller area network adaptor card to communicate with interface boards 44 and the controller area network bus. These communications can auto-terminate the bus, provide a unique node address for each of interface boards 44, and distribute power to interface boards 44. A unique node address is needed by each interface board 44 so that control system 2 can distinguish each sort destination, sensor, and indicator from the others. Further, interface boards 44, in conjunction with the controller area network adaptor

card, are used by control system 2 to communicate with first indicator 28, push-button indicator 30 and alert indicator 32, scale 24. By communicating with these, control system 2 can, for instance, visually instruct the user where to place the object. Control system 2 also uses interface boards 44 to communicate with object placement sensor 26 and a crate placement sensor, which is preferably scale 24, for each sort destination. By so doing, control system 2 could, for example, learn that an object or empty crate was placed within a specific sort destination. Thus, interface boards 44 light up each set of indicators 28, 30, and 32 and monitor if any of them have been pressed. Interface boards 44 preferably communicate with control system 2 through the controller area network bus at a rate of 250 kbp/s to enable objects to be sorted quickly. In addition, control system 2 is preferably connected to Ethernet connection 46 for communication between control system 2 and at least one external device and serial port 48 for communication between control system 2 and at least one diagnostic system. These are preferred because they allow control system 2 to update a scan central server 154 and to be checked for flaws.

The object sorting system preferably also includes, when the quantity of objects to be sorted requires additional sort destinations, additional expansion racks 14. Expansion racks 14 are preferably just like primary racks 12 of rack system 10 already discussed. When rack system 10 includes expansion racks 14, the management system includes a second controller area network addressing board 50 and a corresponding number of second controller area network interface boards 52 for each expansion rack 14. Like without expansion racks 14, the addressing

boards (50, in this case of expansion racks 14) can auto-terminate the bus, provide a unique node address for each interface board 52, and distribute power to interface boards 52. Likewise, each interface board 52 controls scale 24, lights 28, 30, and 32, and object placement sensor 26 for its sort destination. Expansion racks 14 are structurally identical to primary rack 12 except that each primary rack 12 comprises twelve sort destination modules 20, but each expansion rack 14 comprises only six sort destination modules 20.

It will be apparent to those skilled in the art that various modifications and variations can be made in the object sorting method and system of the present invention and in construction of this system without departing from the scope or spirit of the invention.

Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.

WHAT IS CLAIMED IS:

1. A method for sorting objects having machine-readable indicia thereon, comprising the steps of:

capturing object information from the machine-readable indicia on an object;

determining routing information from the object information;

determining, based on the routing information, a correct sort destination for the object;

and

generating a visual and/or audio command identifying the correct sort destination for the object.

2. The method of claim 1, wherein the object information is captured as the object moves on a conveyor belt.

3. The method of claim 1, wherein the object information is captured as the object moves with manual assistance.

4. The method of claim 1, further comprising the step of measuring the weight of the object by weighing the correct sort destination containing the object.

5. The method of claim 1, wherein the generating a visual and/or audio command identifying the correct sort destination for the object is performed by illuminating an indicator near the correct sort destination.
6. The method of claim 1, further comprising the step of verifying that the object has been placed into the correct sort destination.
7. The method of claim 6, wherein the verifying step is performed using a photo sensor, motion detector, or scale.
8. The method of claim 6, further comprising the step of generating visual and/or audio commands if the object is not placed into the correct sort destination.
9. The method of claim 8, wherein the step of generating visual and/or audio commands is performed by illuminating an indicator near an incorrect sort destination into which the object was placed.
10. The method of claim 8, further comprising repeating the previous steps for each subsequent object.

- 5
11. The method of claim 10, further comprising the steps of:
- recording when the object is placed in the correct sort destination;
 - recording when the object is placed in an incorrect sort destination;
 - recording when a sort is started and stopped; and
 - calculating, based on the recorded times, a sort rate, a sort idle time, a sort accuracy, and a total number of objects processed.
12. The method of claim 11, further comprising the steps of creating a record including the routing information for each object, the weight of each object, the sort rate, the sort accuracy, the idle time, the sort start and stop time, and the number of the objects processed.
13. The method of claim 12, further comprising the steps of:
- uploading the record to a database; and
 - transmitting data from the database to one or more of an object tracking database, a billing database, and a scan central server.
14. The method of claim 1, further comprising the step of capturing an operator's identity.

15. The method of claim 1 wherein the determining routing information from the object information is performed by comparing the object information to a local or remote database that contains the routing information associated with the object information.

16. An object sorting system comprising:

a rack system comprising a plurality of sort destination modules, each sort destination module further comprising a sort destination for holding at least one object; and

a management system comprising:

a control system;

an information capture device for reading machine-readable indicia from each object and for outputting the information to the control system; and

an audio system and/or visual indicators for providing instructions to an operator.

17. The object sorting system of claim 16 wherein the sort destination modules further comprise at least one indicator identifying that an object should be placed in the sort destination and wherein the control system is capable of outputting a signal to the at least one indicator for each of the plurality of sort destination modules.

009301-2627563

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, D. C. 20005
202-408-4000

19. The object sorting system of claim 16 wherein the sort destination modules further comprise a scale for weighing the sort destination and wherein the control system is capable of inputting and recording the weight of the sort destination containing the object.

outputting a signal to the at least one indicator for each of the plurality of sort destination modules;

inputting information from the at least one placement sensor for each of the plurality of sort destination modules;

determining which sort destination the object was placed in and when the object was placed in the sort destination; and

inputting and recording the weight of the sort destination containing the object.

21. The object sorting system of claim 20 wherein the management system further comprises a user interface.

22. The object sorting system of claim 21, wherein the user interface is capable of being used to input an operator's identity and to output the operator's identity to the control system.

23. The object sorting system of claim 20 wherein each of the plurality of sort destination modules further comprises:

a crate placement sensor for monitoring whether a crate is within the sort destination, and

a second indicator for indicating when a crate should be changed based upon a predetermined parameter associated with the crate.

24. The object sorting system of claim 23, the rack system further comprising:
- a controller area network bus for communicating with the control system and a controller area network addressing board; and
 - a controller area network adaptor card for communication between the control system, the controller area network bus, and a plurality of interface boards.

25. The object sorting system of claim 24, wherein the controller area network adaptor card is capable of communicating with at least one of the plurality of interface boards and the controller area network bus, auto-terminating the bus, providing a unique node address for each of the plurality of interface boards, and distributing power to the interface boards.

26. The object sorting system of claim 25, wherein the controller area network adaptor card is capable of communicating with the interface boards, each interface board communicating with the first indicator, the second indicator, and the scale, and additionally capable through additional I/O ports to interface with the sort destination placement sensor and the object placement sensor.

27. The object sorting system of claim 26, wherein the interface boards communicate with the control system through the controller area network bus.

28. The object sorting system of claim 20, the management system further comprising:
an Ethernet connection for communication between the control system and at least one external device; and
a serial port for communication between the control system and at least one diagnostic system.

29. The object sorting system of claim 20, where each placement sensor includes a proximity-type sensor.

30. The object sorting system of claim 20, where each of the first indicators are mounted near the front-side of each sort destination, and each of the second indicators are mounted near the back-side of each sort destination.

31. The method of claim 1, wherein the object information is captured as the object moves with mechanical assistance.

5

170

```

graph TD
    106[106 Initialize System Process] --> 108[108 Login User]
    108 --> 110[110 Sort Selection / SD Initialization Process]
    110 --> 112{{112 Idle State}}
    112 --> 114[114 User Interface Options]
    112 --> 102[102 Capture Indicia on Object / Lookup Routing Process]
    112 --> 122[122 Misplaced Object Correction Process]
    112 --> 104[104 Object Placement / Weighing Process]
    112 --> 148[148 Sort Destination Close-out Process]
    112 --> 124[124 Object Database and Upload Process]
    114 --> 112
    102 --> 104
    104 --> 120[120 Tare Process]
    104 --> 122
    104 --> 124
    120 --> 104
    122 --> 102
    124 --> 148
    148 --> 150[150 End Sort Process]
    150 --> 126[126 Sort Completed]
    126 --> 108

```

Figure 1

106




Figure 2

110




Figure 3

128

Capture Indicia from Object

130

Extract Object Information
from Indicia; use to determine
Routing and correct Sort Destination

132

Generate command Identifying
to Operator correct Sort Destination

134

Verify Placement of Object into
Correct Sort Destination

Figure 4

Variable	Mean	SD	Min	Max
Age	34.5	10.2	22	55
Gender	0.5	0.5	0	1
Marital Status	0.6	0.5	0	1
Education	12.5	1.5	9	16
Income	1500	500	500	3000
Health Status	0.8	0.2	0	1
Employment Status	0.7	0.3	0	1
Family Size	3.2	1.1	1	6
Home Ownership	0.9	0.1	0	1
Vehicle Ownership	0.6	0.5	0	1
Life Satisfaction	4.5	1.2	1	7
Stress Level	3.8	1.5	1	6
Work-Life Balance	5.2	1.0	3	7
Community Involvement	2.1	0.8	0	4
Financial Stability	4.0	1.1	1	6
Healthcare Access	5.5	0.9	3	7
Education Quality	6.0	0.8	4	7
Employment Opportunities	5.8	1.0	3	7
Infrastructure Development	6.5	0.7	4	7
Environmental Quality	6.2	0.9	4	7
Social Services	5.9	1.0	3	7
Public Safety	6.1	0.8	4	7
Healthcare Quality	6.3	0.7	4	7
Education Access	6.4	0.6	4	7
Employment Stability	6.2	0.9	4	7
Infrastructure Quality	6.6	0.8	4	7
Environmental Stability	6.4	0.7	4	7
Social Stability	6.1	0.9	4	7
Financial Access	6.0	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality	6.2	0.7	4	7
Education Access	6.3	0.6	4	7
Employment Stability	6.1	0.9	4	7
Infrastructure Quality	6.5	0.8	4	7
Environmental Stability	6.3	0.7	4	7
Social Stability	6.0	0.9	4	7
Financial Access	6.1	0.8	4	7
Healthcare Quality</				




Figure 5

102




Figure 6

104




Figure 7

122




Figure 8

120




Figure 9

148

148-01

User Interface options to initiate SD Close out
By Weight, Sorter Button or Quarterback Button
Sorter can not sort new objects to this SD

148-02

Is the SD waiting
for an Object Placement
or Weight

Yes

148-03

Wait until the SD
receives placement
message and/or
Object weight

No

148-04

Quarterback Light
illuminates solid

148-05

Quarterback removes
crate

148-06

Scale checks
weight and senses
crate removed

No

Yes

148-07

System sends signal
to SD light to fast
flash

148-08

Quarterback pushes
the SD button

148-09

Print the CONS TAG
and SD light continues
fast flash

148-10

Update
database

148-11

Has printer
completed printing

No

Yes

148-14

Quarterback places
new crate in the SD

148-13

SD Light starts to
flash slow

148-12

Scale determines
if empty crate has be
place in SD

No

Yes

148-15

SD light goes off

148-16

Sorter is allowed to
sort objects to this
SD again

148-17

Is this an End Sort?

No

Yes

148-18

Return IDLE process

150

Return to End Sort
Process

Figure 10

124




Figure 11

150




Figure 12




Figure 13




Figure 14

